Page 80f8 HOT STICKS MODEL HS ± 6D INSIDE THE CASE & METER-SCALE





MODEL HS ± 6D	SPECIFICATIONS
TERMINATIONS	One probe terminates with a hook & one with a spike. Each is 89 cm (35 inches)
MAX. VOLTAGE READING	Zero to plus 6 kV dc & zero to minus 6 kV dc Max. Current leakage: 1 mA from probe to probe
CARRYING CASE	Case model HSC, is made of strong ABS material. It is c/w carrying handles & soft foam on the inside to protect the sticks
For additional information	Please call: 416-299-6666 In Canada & USA only: 1-800-268-6886

Page 10f8 HOT STICKS MODEL HS-15 INSIDE THE CASE & METER-SCALE





MODEL HS-15	SPECIFICATIONS
TERMINATIONS	One probe terminates with a hook & one with a spike. Each is 89 cm (35 inches)
MAX, VOLTAGE READING	0-15 kV ac. Max. Current leakage: 1 mA from probe to probe
CARRYING CASE	Case model HSC, is made of strong ABS material. It is c/w carrying handles & soft foam on the inside to protect the sticks
For additional information	Please call: 416-299-6666 In Canada & USA only: 1-800-268-6886

Page 50f8

HOT STICKS

MODEL HS-35 INSIDE & OUTSIDE THE CASE & METER-SCALE







MODEL HS-35	SPECIFICATIONS
TERMINATIONS	One probe terminates with a hook & one with a spike. Each is c/w an extension which makes the total length 167 cm (66 in)
MAX. VOLTAGE READING	0-35 kV ac. Max. Current leakage: 1 mA from probe to probe
CARRYING CASE	Case model HSC, is made of strong ABS material. It is c/w carrying handles & soft foam on the inside to protect the sticks
For additional information	Please call: 416-299-6666 In Canada & USA only: 1-800-268-6886

Page 70f8

HOT STICKS

MODEL HS-50 INSIDE & OUTSIDE THE CASE & METER-SCALE







MODEL HS-50	SPECIFICATIONS
TERMINATIONS	One probe terminates with a hook & one with a spike. Each is c/w an extension which makes the total length 167 cm (66 in)
MAX. VOLTAGE	0-50 kV ac. Max. Current leakage: 1 mA
READING	from probe to probe
CARRYING CASE	Case model HSC, is made of strong ABS material. It is c/w carrying handles & soft foam on the inside to protect the sticks
For additional	Please call: 416-299-6666
information	In Canada & USA only: 1-800-268-6886

Page 2 0f 8 PHASING STICKS
MODEL HSL-15 INSIDE THE CASE & METER-SCALE





MODEL HSL-15	SPECIFICATIONS
TERMINATIONS	One probe terminates with a hook & one with a spike. Each is 89 cm (35 inches)
MAX. VOLTAGE READING	0-15 kV ac. Max. Current leakage: 1 mA from probe to probe. The scale is expended at the beginning to make it easy to read close to zero
CARRYING CASE	Case model HSC, is made of strong ABS material. It is c/w carrying handles & soft foam on the inside to protect the sticks
For additional information	Please call: 416-299-6666 In Canada & USA only: 1-800-268-6886

Page 60f8 PHASING-STICKS

MODEL HSL-35 INSIDE & OUTSIDE THE CASE & METER-SCALE







MODEL HSL-35	SPECIFICATIONS
TERMINATIONS	One probe terminates with a hook & one with a spike. Each is c/w an extension which makes the total length 167 cm (66 in)
MAX. VOLTAGE READING	0-35 kV ac. Max. current leakage:1 mA from probe to probe. The scale is expended at the beginning to make it easy to read close to zero
CARRYING CASE	Case model HSC, is made of strong ABS material. It is c/w carrying handles & soft foam on the inside to protect the sticks
For additional information	Please call: 416-299-6666 In Canada & USA only: 1-800-268-6886