

**FRESHPOINT**
**GRO-575B, GRO-575M  
5 STAGE REVERSE OSMOSIS SYSTEMS**


GRO-575B System



GRO-575M Monitored System

**FEATURES/BENEFITS**

High efficiency GRO 75 GPD membrane technology

Effortless click-in lock cartridge installation

3/8" push fit plumbing connection for easy installation and high flow

Water supply valve shut off fits multiple piping styles

Color coded cartridges to maintain proper filter sequence

Lead, chemical and VOC reduction cartridge

3/8" tubing to storage tank and faucet

Built-in check valve with multi-point backflow protection

Utilizes the dual technology of the DFX Diamond Flow series combining a sediment and carbon block in one cartridge

Faucet with air gap included

On board TDS monitor measures rejection of GRO element within GRO-575M model

Includes high performance VOC carbon block filters

**SPECIFICATIONS**

Temperature Range:	40-100°F (4.4-37.8°C)
Pressure Range:	40-100 psi (2.75-6.89 bar)
System Production Rate:	21.08 gpd (79.77 Lpd)
Recovery Rating:	41.05%
Efficiency Rating:	23.57%
TDS Rejection:	96.3%
Dimensions:	17.82"W x 5.46"D x 12.54"H (453mm x 139mm x 319mm)
Weight:	Model: GRO-575B, GRO-575M (system only) 10.7 lbs (4.8 kg)

**PRICE**

GRO-575B	\$650.00	Fridge Hook-up	\$25.00+
GRO-575M	\$800.00	Stone Counter Top	\$85.00+
Installation	\$125.00+		