

This Dielectric Strength Tester is ideal for testing control panels, transformers, electrical motors, home-appliances, lighting fixtures, electrical cables and components.



**DIELECTRIC STRENGTH TESTER
MODEL AVC-50V**

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-5 kV ac @ 95 mA
TRANSFORMER	Rated 500 VA Short duty cycle
VOLTMETER	0-5 kV ac Accuracy: $\pm 2\%$ of full scale
TRIP CURRENT	Adjustable 3-95 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off circuit-breaker, one fuse, one reset push-button, one high-voltage adjust knob, one trip current adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	36W x 24D x 18H cm (14W x 9.5D x 7H inches)
WEIGHT	11 kg (24 lb)

This Dielectric Strength Tester is ideal for testing control panels, small transformers, small electrical motors, home-appliances and other electrical products.



DIELECTRIC STRENGTH TESTER MODEL AVC-50VA

INPUT	120 V 60 Hz
OUTPUT	Adjustable 0-5 kV ac @ 95 mA
TRANSFORMER	Rated 500 VA
VOLTMETER	0-5 kV ac Accuracy: \pm 2% of full scale
AMMETER	0-100 mA ac Accuracy: \pm 2% of full scale
TRIP CURRENT	Adjustable 3-95 mA
INDICATORS	4 Lights (Power-on, high-voltage-on, fault and line-fault)
CONTROL	One on/off circuit-breaker, one fuse, one reset push-button, one high-voltage adjust knob, one current adjust knob and safety device for faulty power-outlet.
LEADS	One input line-cord, one ground lead and one high-voltage lead C/W a retractable probe. Each is 2 meters (6 ft) long.
SIZE	36W x 24D x 18H cm (14W x 9.5D x 7H inches)
WEIGHT	11 kg (24 lb)