

TECHNICAL DATA SHEET

Current Issue Date: January 11, 2010



PlastiSolv 842 Press Wash

Special Features:

PlastiSolv 842 has no odor which makes the job of color changes and screen reclaiming much more pleasant. PlastiSolv 842 dries fast . . . providing a safe, odor-free alternative to mineral spirits, aerosol screen opener and other hot, hazardous, flammable solvents.

PlastiSolv 842 will not "lock in" photopolymer emulsions and films which allows for quick, easy reclaiming. PlastiSolv 842 contains no hazardous substances (no TLV's, no PEL's) which provides a better workplace environment.

PlastiSolv 842 is non-flammable (flash point of 142°F) which makes it safer for handling, storage and rag disposal than conventional solvents.

PlastiSolv 842 is not SARA (Superfund Amendments Reauthorization Act) reportable which requires less solvent monitoring and paperwork.

PlastiSolv 842 may be applied manually, recirculated through the EasiFlo™ System or recirculated in enclosed, automatic screen washing systems, providing superior product life and economy.

HAZARDS IDENTIFICATION

Potential Health Effects:

Eye: Eye contact may cause slight irritation with discomfort.

Skin: Skin contact may cause slight irritation.

Swallowing: Ingestion may cause abdominal discomfort.

Inhalation: Inhalation may cause irritation of the nose and throat with coughing or discomfort.

Application:

Scrape all excess ink from screen.

Apply PlastiSolv 842 Press Wash by squirt bottle, pneumatic sprayer or by rag to the (well) ink side of the screen. Thoroughly agitate ink with a rag or scrubber, then wipe up all dissolved ink.

Reapply if necessary and follow with a dry rag, wipe on both sides of the screen.

The screen will be ready for printing or tape application within 10 - 15 seconds.

HANDLING AND STORAGE

Handling: Avoid breathing vapor or mist. Wash thoroughly after handling.

Storage: Store in a well ventilated location. Avoid temperature