



# DIFFUSION MEDIA FF-560 GX (M5)

- **FINAL FILTRATION** barrier to paint damaging particles from the air intake stream
- **SELF EXTINGUISHING** according **DIN 53438-F1**
- **100% ADHESIVE SATURATION FOR MAXIMUM PROTECTION**
- **R0 RATING ON PARTICLE MIGRATION**
- **HIGH TEMPERATURE RESISTANT SCRIM** up to 350°F
- **QUALITY ASSURANCE** according EN 779:2012

## DESCRIPTION

Fine air filtration media specifically designed to be used in down-draft paint spray booths as final filtration barrier to all paint damaging particles from the intake air stream. This ceiling filter or diffusion media ensures a uniform air distribution and a laminar flow throughout the spray booth, when applied in auto assembly plants and auto refinishing facilities as well as in the repair after markets.

Synthetic fiber-based filter media developed and manufactured at Filtrair's high-tech media plant based in The Netherlands. The filter media is constructed from selected high performance, nonbreakable fibers in a progressive density multi-layering technique allowing high depth loading to ensure high dust holding capacity with optimal lowest pressure drop performance.

This media is thermally bonded and impregnated in full depth with a special tackifier coating to prevent any release of fibers and migration of paint damaging particles larger than 10 microns due to vibration in the system, even under varying temperature conditions.

FF-560 GX is classified as R0 in accordance with the Filtrair migration test (see back page).

This results in high fractional efficiency combined with a high-dust loading capacity, a long filter life as well as low energy and maintenance costs.

## HIGH TEMPERATURE SCRIM

The clean air side is particularly dense and smoothened. It is reinforced with a high temperature resistant and supporting woven open-mesh scrim. The temperature resistance of this special scrim is up to 350°F to prevent any discoloring.

## FLAMMABILITY RATINGS

FF-560 GX conforms to European Union standards (e.g. DIN53438-F1) and is self extinguishing.

It is resistant to evaporated solvents and is manufactured in a 100% silicone-free environment.

## QUALITY ASSURANCE

Constant quality is assured by quality control testing according to EN-779:2012. The M5 filter class and the Filtrair logo with brand name are imprinted on the media.

## FEATURES AND BENEFITS

- **USED BY MAJOR AUTOMOTIVE MANUFACTURERS** so it can be used with complete confidence.
- **FULL PENETRATION OF SPECIAL ADHESIVE** prevents any release of fibers and migration of particles larger than 10 microns.
- **GRADIENT DENSITY STRUCTURE** ensures a uniform air distribution and laminar flow throughout the spray booth.

## APPLICATIONS

This high quality Filtrair ceiling or diffusion media is specially designed to be used in the ceiling of paint spray facilities in auto assembly plants and down draft spray cabins in auto refinishing facilities as well as in paint spray booths of the repair after markets.

This media enhances a uniform air distribution and a laminar airflow. Further, it acts as the final filtration barrier to paint damaging particles from the air stream which is an absolute requirement for high gloss and high-tech performance finishes.

# DIFFUSION MEDIA FF-560 GX (M5)


## TECHNICAL DATA

Product	Unit	FF-560 G
Rated air flow	cfm	530
Air velocity	fpm	50
Initial pressure drop	"w.g.	0.10
Final pressure drop	"w.g.	1.81
Filter class per EN779:2012	-	M5
Average Arrestance	%	96
Average Efficiency (@0.4 µm)	%	46
Dust holding capacity (Ashrae dust) 450 Pa	oz/ft <sup>2</sup>	163

## APPLICATION PARAMETERS

Product	Unit	FF-560 G
Temperature resistance, constant	°F	≤ 210
Temperature resistance, short peaks	°F	< 350
Nominal thickness	inch	0.87
Relative humidity	%	100
Regenerable/washable	-	no
Roll sizes standard		40" x 67' 80" x 67'


## FILTRAIR MIGRATION TEST




Filtrair Migration Test Classes	No. of particles(*)
R0	< 100
R1	< 1.000
R2	< 10.000
R3	< 100.000

(\*) Number of particles larger than 10 microns per cubic meter counted on the clean air side


## PRESSURE DROP vs AIR FLOW RATE



## FRACTIONAL PARTICLE SIZE EFFICIENCY



## DUSTLOADING vs PRESURE DROP vs EFFICIENCY



All data are average indicative values with usual manufacturing and testing tolerances. We reserve the right to modify performance data without prior notice. Specific performance data will require our written confirmation. Filtrair® is the registered trade mark of Filtrair bv.

