

P33 - FOUNTAIN SOLUTION MIXING SYSTEM



This unit is an accurate fountain solution mixing system for single or multipress applications. It features a positive displacement metering pump, a drum level probe and suction tube assembly. It can be connected to any other brand of recirculator with the addition of a float control valve in its reservoir. It features stainless steel components to accommodate aggressive fountain solutions. In addition, it has a metering pump to handle up to 240GPD of pure dampening solution consumption rates of larger pressrooms.



**Enlarged View
of Face Plate**

Features:

- High accuracy mixing repeatability $\pm 1\%$
- Low level additive drum alarm and shut off
- Flashing alarm beacon
- Wall mount is standard
- Stainless steel plumbing
- Feed water pressure gauge
- Single additive

Benefits:

- Capacity up to 240 USGPH (908 lph) of mixed fountain solution
- Can be used as a central mixing system

Options:

- Remote tank unit (with solenoid valve & level controller)
- Single delivery system 35 GPM - 50 PSI pump, pressure switch and bladder tank
- Dual delivery system 35 GPM - 50 PSI pump, pressure switch and bladder tank
- Storage tank 60 gallons (227 liters)
- Storage tank 100 gallons (378 liters)
- Storage tank 200 gallons (757 liters)
- Storage tank 500 gallons (1892 liters)
- Second additive

Technical Data

Voltage: 110-240V / 50-60Hz / 1ph
Dimension: L=12" W=20" H=45"
Weight: Approximately 70Lbs

MASTER FLO
Technology Inc.

154 Seale Road, Wentworth, QC J8H 0G9 (Canada)
Tel: (450) 533-0088 Fax: (450) 533-4597
Web site: www.mflo.com Email: sales@mflo.com